

**Ekspluatācijas īpašību deklarācija Nr. CPR-IT4 / B0361
REV.09/07/2019**

- 1) Unikāls produkta tipa identifikācijas kods: ELASTOFLEX SA P
- 2) Paredzētais pielietojums: Armēta bitumena loksnes Jumta hidroizolācijai
- 3) Ražotājs: **POLYGLASS S.P.A Via Dell'Artigianato, 34-31047 Ponte di Piave (TV) ITALIA - www.polyglass.com**
- 4) Sistēma VVCP: Sistēma 2+

Sistēma 3, uguns reakcijas noteikšanai

- 5) Vienotais standarts: EN 13707:2004 + A2:2009
Izpildinstitūcijas:
Izpildinstitūcija nr. BUREAU VERITAS Nr. 1370, veikusi sākotnējo ražotnes un ražošanas kvalitātes kontroles un uzraudzības pārbaudi, novērošanu un novērtēšanu un ir izsniegusi rūpnīcas ražošanas kontroles atbilstības sertifikātu.

Laboratorija EMI, N.1417, veikusi veikspējas novērtējumu (uguns reakcija), pamatojoties uz testa paraugiem, ko iesniedzis ražotājs.

- 6) Deklarētās veikspējas īpašības:

Būvniecības raksturlielumi	Ekspluatācijas īpašības
Ārējā uguns noturība	NPD
Uguns reakcija	Klase E
Ūdensnecaurlaidība (B metode)	Atbilst prasībām
Stiepes īpašības Stiepes stiprība (gareniski / šķērsvirzienā) Pagarinājums (gareniski / šķērsvirzienā)	400/300 ($\pm 20\%$) N/50 mm 35/35 ($\pm 15\%$) %
Noturība pret sakņu ieaugšanu	NPD
Izturība pret statisko slodzi (A metode)	≥ 10 Kg
Izturība pret triecieniem (A metode)	≥ 400 mm
Izturība pret plīsumiem (gareniski / šķērsvirzienā)	150/150 ($\pm 30\%$) N
Savienojumu šuvju stiprība Noturība pret stiepi Noturība pret bīdi	NPD NPD
Mākslīgās novecināšanas izpausmes: Plūsmas izturība paaugstinātā temperatūrā Elastīgums zemā temperatūrā Izturība (pēc QUV): Redzami defekti	≥ 100 °C ≤ -10 °C Atbilst prasībām
Elastīgums zemā temperatūrā	≤ -20 °C
Bīstamas sastāvdaļas	NPD

Saskaņā ar REACH regulu (EK) Nr. 1907/2006, šis ir izstrādājums, un saskaņā ar šīs regulas 31. un 33. punktu, produktam drošības datu lapas nav nepieciešamas. Lietojot izstrādājumu, pievērst uzmanību tehnisko datu lapā dotajiem ieteikumiem un darba vietā noteiktajām drošības prasībām

Augstāk norādītā produkta veikspēja atbilst deklarētajām īpašībām.

Šī ekspluatācijas īpašību deklarācija ir izsniegta saskaņā ar Regulu (ES) Nr 305/2011, ar pilnu iepriekš norādītā ražotāja atbildību.

Parakstīts ražotāja vārdā: [Ing. P. Ciferni](#)

In Ponte di Piave 09/07/2019

.....

EĪD PDF formātā ir pieejamas Polyglass SpA mājas lapā.

2. versija:	Nemainīgs produkts, atjaunota EID forma
-------------	---

 1370 1417	 Via Dell'Artigianato, 34 31047 Ponte di Piave (TV) ITALIA - www.polyglass.com
14 CPR-IT4/ B0361 rev. 17/04/2019 EN 13707 ELASTOFLEX SA P <i>Reinforced bitumen sheet for roof waterproofing</i>	
Reaction to fire	Classe E
Watertightness (Method B)	Meet requirements
Tensile properties Tensile strength (longitudinal/transverse) Elongation (longitudinal/transverse)	400/300 (±20%) N/50 mm 35/35 (±15) %
Resistance to static loading (Method A)	≥ 10 Kg
Resistance to impact (Method A)	≥ 400 mm
Resistance to tearing (longitudinal/transverse)	150/150 (±30%) N
Artificial ageing behaviour: Flow resistance at elevated temperature Flexibility at low temperature Durability (after QUV): Visible defects	≥ 100 °C ≤ -10 °C Meet requirements
Flexibility at low temperature	≤ -20 °C
Dangerous substances	NPD

Note:

MAPEI nodrošina šo pielikumu kopā ar EĪD, lai atvieglotu CE marķējuma skaidrojumu starptautiskajiem klientiem. Pievienotais CE marķējums var būt nedaudz atšķirīgs, salīdzinot ar to, kas norādīts uz attiecīgā iepakojuma vai dokumentācijas, jo:

- Dēļ grafiskā pielāgojuma uz iepakojuma vai izmantotās drukāšanas metodes,
- Dēļ valodu atšķirības (viens iepakojums vairākām valstīm),
- produkts ir jau krājumā uz brīdi, kad tiek ieviests CE marķējuma atjauninājums,
- Drukas kļūdas dēļ.

Declaration of performance N. CPR-IT4/ B0361 rev. 09/07/2019

- 1) Unique identification code of the product-type: ELASTOFLEX SA P
- 2) Intended uses: Reinforced bitumen sheet for roof waterproofing
- 3) Manufacturer: POLYGLASS S.P.A Via Dell'Artigianato, 34-31047 Ponte di Piave (TV) ITALIA - www.polyglass.com
- 4) System of VVCP: System 2 +

System 3 (reaction to fire)

- 5) Harmonized standards: EN 13707:2004 + A2 :2009

Notified bodies:

The Notified Body BUREAU VERITAS, N. 1370 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of conformity of the factory production control.

The notified laboratory EMI, N.1417, carried out the assessment of the performance (reaction to fire) on the basis of testing on samples taken by the manufacturer.

- 6) Performances declared:

Essential characteristics	Performances
External fire performance	NPD
Reaction to fire	Classe E
Watertightness (Method B)	Meet requirements
Tensile properties Tensile strength (longitudinal/transverse) Elongation (longitudinal/transverse)	400/300 ($\pm 20\%$) N/50 mm 35/35 ($\pm 15\%$) %
Root resistance	NPD
Resistance to static loading (Method A)	≥ 10 Kg
Resistance to impact (Method A)	≥ 400 mm
Resistance to tearing (longitudinal/transverse)	150/150 ($\pm 30\%$) N
Joint strenght Peel resistance Shear resistance	NPD NPD
Artificial ageing behaviour: Flow resistance at elevated temperature Flexibility at low temperature Durability (after QUV): Visible defects	≥ 100 °C ≤ -10 °C Meet requirements
Flexibility at low temperature	≤ -20 °C
Dangerous substances	NPD


This is an article in accordance with Article 3 of the REACH regulation (EC) no. 1907/2006 and pursuant to Article 31 and 33 of the a/m regulation does not require any Safety Data Sheet. While using the product, pay attention to the recommendations written in the Technical Data Sheet and to the safety requirements laid down in the workplace

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: [Ing. P. Ciferni](#)

[In Ponte di Piave 09/07/2019](#)


.....

DoP in Pdf format are available in the Polyglass SpA website.

Version 2:	Unchanged product, DoP layout updated
------------	---------------------------------------

 1370 1417	 Via Dell'Artigianato, 34 31047 Ponte di Piave (TV) ITALIA - www.polyglass.com
14 CPR-IT4/ B0361 rev. 09/07/2019 EN 13707 ELASTOFLEX SA P <i>Reinforced bitumen sheet for roof waterproofing</i>	
Reaction to fire	Classe E
Watertightness (Method B)	Meet requirements
Tensile properties Tensile strength (longitudinal/transverse) Elongation (longitudinal/transverse)	400/300 (±20%) N/50 mm 35/35 (±15) %
Resistance to static loading (Method A)	≥ 10 Kg
Resistance to impact (Method A)	≥ 400 mm
Resistance to tearing (longitudinal/transverse)	150/150 (±30%) N
Artificial ageing behaviour: Flow resistance at elevated temperature Flexibility at low temperature Durability (after QUV): Visible defects	≥ 100 °C ≤ -10 °C Meet requirements
Flexibility at low temperature	≤ -20 °C
Dangerous substances	NPD

Note:

Polyglass supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- *graphic adaptations due to lack of space on the packaging or printing methods used,*
- *different language (the same packaging can be shared by several countries),*
- *the product is already in stock when the updating of the CE marking is implemented,*
- *printing mistakes.*