

**Ekspluatācijas īpašību deklarācija Nr. CPR-IT4 / S1546
REV.08/10/2021**

- 1) Unikāls produkta tipa identifikācijas kods: **MAPEPLAN UG 15**
- 2) Paredzētais pielietojums: **Elastīgs hidroizolācijas materiāls pret mitrumu iekļūvi ēkās, kā arī ēkas pazemes hidroizolēšanai.**
- 3) Ražotājs: **POLYGLASS S.P.A Via Giorgio Squinzi, 2 -31047 Ponte di Piave (TV) ITALIA - www.polyglass.com**
- 4) Sistēma VVCP:
Sistēma 2+
Sistēma 3, uguns reakcijas noteikšanai
- 5) Vienotais standarts: **EN 13967-1:2012**
Izpildinstitūcija:
BUREAU VERITAS ITALIA S.P.A. N. 1370
TECNO PIEMONTE SPA N. 1372

6) Deklarētās ekspluatācijas īpašības:

Būtiskākie raksturlielumi	Ekspluatācijas īpašības
Uguns reakcija	E Klase
Ūdens necaurlaidība	Atbilst
Plīsuma noturība	Caurduršana ar naglu L / T : ≥ 300 N
Šuvju stiprība	Savienojuma vietu bīdes noturība: ≥ 800 N/50mm
Trieciennoturība	≥ 500 mm [Met. A] ≥ 1100 mm [Met. B]
Stiepes stiprība	Stiepes izturība (L/T): $15 (\pm 2)$ N/mm² [Met. B] Pagarinājums līdz plīsumam L / T: $280 (\pm 10\%)$ %
Noturība pret statisko noslodzi	≥ 25 Kg (Met. B)
Ilgmūžība	Ūdensnecaurlaidība pēc mākslīgās novecināšanas: Atbilst Ūdensnecaurlaidība pēc ķīmisku vielu iedarbības: Atbilst
Bīstamas sastāvdaļas	NPD

Augstāk norādītā produkta veiktspēja atbilst deklarētajām īpašībām.

Šī ekspluatācijas īpašību deklarācija ir izsniegta saskaņā ar Regulu (ES) Nr 305/2011, ar pilnu iepriekš norādītā ražotāja atbildību.

Parakstīts ražotāja vārdā: **Ing. P. Ciferri** In **Ponte di Piave**,
08/10/2021

REACH informācija: šis ir izstrādājums saskaņā ar REACH Regulas (EK) Nr. 1907/2006 un saskaņā ar iepriekš minētās regulas 31. un 33. pantu neprasa nekādu drošības datu lapu. Lietojot izstrādājumu, pievērst uzmanību tehnisko datu lapā dotajiem ieteikumiem un darba vietā noteiktajām drošības prasībām

DoP ir pieejams Pdf formātā Polyglass SpA vietnē.

Versija: 0	Nemainīts produkts. Ražotāja kontaktadrese ir atjaunināta.
-------------------	---

 1370 1372	 POLYGLASS S.P.A Via Giorgio Squinzi, 2 -31047 Ponte di Piave (TV) ITALIA - www.polyglass.com
14 CPR-IT4/S1546 rev. 08/10/2021 EN 13967:2012 MAPEPLAN UG 15 Flexible plastic sheet for damp proofing in buildings, including basement tanking.	
Reaction to fire	Class E
Watertightness	Pass
Tear resistance	Nail tearing L / T : ≥ 300 N
Joint strength	Joint shear resistance: ≥ 800 N/50mm
Impact resistance	≥ 500 mm [Met. A] ≥ 1100 mm [Met. B]
Tensile strength	Tensile strength L / T : $15 (\pm 2)$ N/mm ² [Met. B] Elongation at break L / T: $280 (\pm 10\%)$ %
Resistance to static loading	≥ 25 Kg (Met. B)
Durability	Watertightness after artificial ageing: Pass Watertightness after exposure to chemicals: Pass
Dangerous substances	NPD

Piezīme:

MAPEI nodrošina šo pielikumu kopā ar EĪD, lai atvieglotu CE marķējuma skaidrojumu starptautiskajiem klientiem. Pievienotais CE marķējums var būt nedaudz atšķirīgs, salīdzinot ar to, kas norādīts uz attiecīgā iepakojuma vai dokumentācijas, jo:

- NPD (Veiktspēja nav noteikta) vērtības var tikt mainītas CE marķējumā
- Dēļ grafiskā pielāgojuma uz iepakojuma vai izmantotās drukāšanas metodes,
- Dēļ valodu atšķirības (viens iepakojums vairākām valstīm),
- produkts ir jau krājumā uz brīdi, kad tiek ieviests CE marķējuma atjauninājums,
- Drukas kļūdas dēļ.

Declaration of performance N. CPR-IT4/S1546 rev. 08/10/2021

- 1) Unique identification code of the product-type: **MAPEPLAN UG 15**
- 2) Intended uses: **Flexible plastic sheet for damp proofing in buildings, including basement tanking.**
- 3) Manufacturer: **POLYGLASS S.P.A Via Giorgio Squinzi, 2 -31047 Ponte di Piave (TV) ITALIA - www.polyglass.com**
- 4) Systems of VVCP:
 - System 2+**
 - System 3 (reaction to fire)**
- 5) Harmonized standards: **EN 13967:2012**
 Notified bodies:
 - BUREAU VERITAS ITALIA S.P.A. N. 1370**
 - TECNO PIEMONTE SPA N. 1372**
- 6) Declared performances:

Essential characteristics	Performances
Reaction to fire	Class E
Watertightness	Pass
Tear resistance	Nail tearing L / T : ≥ 300 N
Joint strength	Joint shear resistance: ≥ 800 N/50mm
Impact resistance	≥ 500 mm [Met. A] ≥ 1100 mm [Met. B]
Tensile strength	Tensile strength L / T: $15 (\pm 2)$ N/mm² [Met. B] Elongation at break L / T: $280 (\pm 10\%)$ %
Resistance to static loading	≥ 25 Kg [Met. B]
Durability	Watertightness after artificial ageing: Pass Watertightness after exposure to chemicals: Pass
Dangerous substances	NPD

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Ing. P. Ciferri**
 In **Ponte di Piave, 08/10/2021**

.....  ..

REACH information: this is an article in accordance with Article 3 of the REACH Regulation (EC) No 1907/2006 and pursuant to Article 31 and 33 of the above-mentioned Regulation does not require any Safety Data Sheet. While using the product, pay attention to the recommendations written in the Technical Data Sheet and to the safety requirements laid down in the workplace.

DoP are available in Pdf format on Polyglass SpA website.

Version: 0	Unchanged product. The manufacturer contact address has been updated.
-------------------	--

 1370 1372	 POLYGLASS S.P.A Via Giorgio Squinzi, 2 -31047 Ponte di Piave (TV) ITALIA - www.polyglass.com
14 CPR-IT4/S1546 rev. 08/10/2021 EN 13967:2012 MAPEPLAN UG 15 Flexible plastic sheet for damp proofing in buildings, including basement tanking.	
Reaction to fire	Class E
Watertightness	Pass
Tear resistance	Nail tearing L / T : ≥ 300 N
Joint strength	Joint shear resistance: ≥ 800 N/50mm
Impact resistance	≥ 500 mm [Met. A] ≥ 1100 mm [Met. B]
Tensile strength	Tensile strength L / T : $15 (\pm 2)$ N/mm ² [Met. B] Elongation at break L / T: $280 (\pm 10\%)$ %
Resistance to static loading	≥ 25 Kg [Met. B]
Durability	Watertightness after artificial ageing: Pass Watertightness after exposure to chemicals: Pass
Dangerous substances	NPD

Note:

POLYGLASS supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- NPD (No Performance Determined) values can be omitted by the CE marking,
- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.



MAPEPLAN UG 15
CE MARKING
Annex to DoP N. CPR-IT4/S1546
rev. 08/10/2021