

EKSPLUATĀCIJAS ĪPAŠĪBU DEKLARĀCIJA N. CPR-PL1/084

- 1) Unikāls produkta tipa identifikācijas kods: NIVOPLAN PLUS
- 2) Paredzētais pielietojums: **Rūpnieciski ražota vispārēja pielietojuma apmetuma java (GP), ārdarbiem un iekšdarbiem, izmantošanai uz sienām, griestiem, kolonnām un starpsienām**
- 3) Ražotājs: **MAPEI Polska Sp. z o.o. ul. Gustawa Eiffel'a 14, 44-109 Gliwice - www.mapei.pl**
- 4) Sistēma AVCP: Sistēma 4
- 5) Vienotais standarts: EN 998-1:2016

Izpildinstitūcijas: Nav nepieciešama izpildinstitūcijas iesaistīšana

- 6) Deklarētās ekspluatācijas īpašības:

Būtiskākie raksturlielumi	Ekspluatācijas īpašības
Uguns reakcija	Klase A1
Ūdens absorbcija	$W_c 1$
Ūdens tvaiku caurlaidības koeficients	$\mu \leq 30$
Adhēzija	$\geq 1,0 \text{ N/mm}^2$ – FP:B
Termālā vadītspēja	0,77 W/mK (tab. vērtība; P=50%)
Izturība (noturība sasalšanas, atkuššanas ciklos):	
- Masas samazināšanās pēc 25 cikliem	$\leq 0,3 \%$
- Lieces stiprības samazinājums	$\leq 8 \%$
- spiedes stiprības samazināšanās	$\leq 3 \%$
Bīstamas vielas	NPD

Augstāk norādītā produkta veiktspēja atbilst deklarētajām īpašībām.

Šī ekspluatācijas īpašību deklarācija ir izsniegta saskaņā ar Regulu (ES) Nr 305/2011, ar pilnu iepriekš norādītā ražotāja atbildību.

Parakstīts ražotāja vārdā: MAPEI Polska Sp. z o.o. Valdes locekle **Veronica Squinzi**

Gliwice, 19/03/2020

EĪD PDF formātā ir pieejamas Mapei mājas lapā

<i>Pārskats 4 piezīmes:</i>	<i>Produkts nav mainīts, veiktspējas apstiprinātas; paredzētais pielietojums modificēts</i>
---------------------------------	---

	 MAPEI Polska Sp. z o.o. ul. Gustawa Eiffel'a 14, 44-109 Gliwice www.mapei.pl
15 CPR-PL1/084 EN 998-1 NIVOPLAN PLUS <i>Factory-made, general purpose rendering mortar (GP) for external and internal use on walls, ceilings, columns and partitions</i>	
Reaction to fire Water absorption Water vapour permeability coefficient Adhesion Thermal conductivity Durability (resistance to freeze-thaw): - mass decrement after 25 cycles - decrease in flexural strength - decrease in compressive strength	Class A1 $W_c 1$ $\mu \leq 30$ $\geq 1,0 \text{ N/mm}^2$ - FP:B $0,77 \text{ W/m}\cdot\text{K}$ (tab. mean value; P=50%) $\leq 0,3 \%$ $\leq 8 \%$ $\leq 3 \%$

DECLARATION OF PERFORMANCE N. CPR-PL1/084

- 1) Unique identification code of the product-type: **NIVOPLAN PLUS**
- 2) Intended use/es: **Factory-made, general purpose rendering mortar (GP) for external and internal use on walls, ceilings, columns and partitions**
- 3) Manufacturer: **MAPEI Polska Sp. z o.o. - ul. Gustawa Eiffel'a 14, 44-109 Gliwice - www.mapei.pl**
- 4) System/s of AVCP: **System 4**
- 5) Harmonized standard: **EN 998-1:2016**

Notified body/ies: **No tasks for notified body**

- 6) Declared performance/s:

Essential characteristics	Performances
Reaction to fire Water absorption Water vapour permeability coefficient Adhesion Thermal conductivity Durability (resistance to freeze-thaw): - mass decrement after 25 cycles - decrease in flexural strength - decrease in compressive strength Dangerous substances	Class A1 W_c 1 $\mu \leq 30$ $\geq 1,0 \text{ N/mm}^2$ - FP:B 0,77 W/m·K (tab. mean value; P=50%) $\leq 0,3 \%$ $\leq 8 \%$ $\leq 3 \%$ NPD

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Veronica Squinzi – Member of the Board of MAPEI Polska Sp. z o.o.**

Gliwice, 19/03/2020


MAPEI POLSKA Sp. z o.o.
Członek Zarządu
This is a CE DoP digitally signed by:

Veronica Squinzi

DoP in Pdf format are available on the Mapei Polska Sp. z o.o. website.

Revision 4 notes:	Product unchanged, performances verified; intended use modified
--------------------------	--

	 MAPEI Polska Sp. z o.o. ul. Gustawa Eiffel'a 14, 44-109 Gliwice www.mapei.pl
15 CPR-PL1/084 EN 998-1 NIVOPLAN PLUS <i>Factory-made, general purpose rendering mortar (GP) for external and internal use on walls, ceilings, columns and partitions</i>	
Reaction to fire Water absorption Water vapour permeability coefficient Adhesion Thermal conductivity Durability (resistance to freeze-thaw): - mass decrement after 25 cycles - decrease in flexural strength - decrease in compressive strength	Class A1 $W_c 1$ $\mu \leq 30$ $\geq 1,0 \text{ N/mm}^2$ - FP:B $0,77 \text{ W/m}\cdot\text{K}$ (tab. mean value; P=50%) $\leq 0,3 \%$ $\leq 8 \%$ $\leq 3 \%$