

EKSPLUATĀCIJAS ĪPAŠĪBU DEKLARĀCIJA N. CPR-IT1/0897

- 1) Unikāls produkta tipa identifikācijas kods: **MAPEFLOOR CPU+/RT**
- 2) Paredzētais pielietojums: **Ar polimēriem modificēts trīskomponentu cementa bāzes grīdu izveides materiāls iekštelpām**
- 3) Ražotājs: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Sistēma AVCP: **Sistēma 4
Sistēma 3, ugunsdrošības noteikšanai**
- 5) Vienotais standarts: **EN 13813:2002**
Izpildinstitūcijas: **CSI SPA, N. 0497**

- 6) Deklarētās veiktspējas īpašības:

Būtiskākie raksturlielumi	Ekspluatācijas īpašības
Uguns reakcija: Kodīgu vielu izdalīšanās: Ūdens caurlaidība: Ūdens tvaiku caurlaidība: Spiedes stiprība: Lieces stiprība: Nodilumizturība: Skaņas izolācija: Skaņas absorbcija: Termiskā pretestība: Ķīmiskā izturība:	Klase B_{FL}-s1 CT w < 0,1 kg/(m²·h_{0,5}) NPD C50 F10 AR0,5 NPD NPD NPD (Shore D samazinājums < 50%) CR9, CR10 (II klase, krāsas maiņa, skaidrāks) CR11, CR12 (II klase)

Augstāk norādītā produkta veiktspēja atbilst deklarētajām īpašībām. Šī ekspluatācijas īpašību deklarācija ir izsniegta saskaņā ar Regulu (ES) Nr 305/2011, ar pilnu iepriekš norādītā ražotāja atbildību.

Parakstīts ražotāja vārdā: **Lorenzo Martino – Korporatīvā Kvalitātes Vadība**

Milāna, 21/12/2022

REACH informācija: informācija, kas minēta REACH Regulas (EK) Nr. 1907/2006 31. punktā vai, attiecīgā gadījumā, 33. punktā un turpmākajos grozījumos, ir norādīti drošības datu lapā, kas pieejama MAPEI mājas lapā, kopā ar šo spēkā esošo Ekspluatācijas īpašību deklarāciju.

EĪD PDF formātā ir pieejamas Mapei mājas lapā

Pārskats 1	Uguns reakcijas klasifikācija atjaunota
-------------------	--

 0497	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
21 CPR-IT1/0897 EN 13813 MAPEFLOOR CPU+/RT <i>Three-component cementitious screed material modified by polymer for internal use in floor construction</i>	
Reaction to fire: Release of corrosive substances: Water permeability: Water vapour permeability: Compressive strength: Flexural strength: Wear resistance: Sound insulation: Sound absorption: Thermal resistance: Chemical resistance:	Class B _{FL} -s1 CT $w < 0,1 \text{ kg}/(\text{m}^2 \cdot \text{h}_{0,5})$ NPD C50 F10 AR0,5 NPD NPD NPD (Shore D reduction < 50%) CR9, CR10 (Class II, change of colour, clearer) CR11, CR12 (Class II)

Piezīme:

MAPEI nodrošina šo pielikumu kopā ar EĪD, lai atvieglotu CE marķējuma skaidrojumu starptautiskajiem klientiem. Pievienotais CE marķējums var būt nedaudz atšķirīgs, salīdzinot ar to, kas norādīts uz attiecīgā iepakojuma vai dokumentācijas, jo:

- NPD (Veiktspēja nav noteikta) vērtības var tikt mainītas CE marķējumā
- Dēļ grafiskā pielāgojuma uz iepakojuma vai izmantotās drukāšanas metodes,
- Dēļ valodu atšķirības (viens iepakojums vairākām valstīm),
- produkts ir jau krājumā uz brīdi, kad tiek ieviests CE marķējuma atjauninājums,
- Drukas kļūdas dēļ.

DECLARATION OF PERFORMANCE N. CPR-IT1/0897

- 1) Unique identification code of the product-type: **MAPEFLOOR CPU+/RT**
- 2) Intended uses: **Three-component cementitious screed material modified by polymer for internal use in floor construction**
- 3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Systems of AVCP: **System 4**
System 3 (for reaction to fire)
- 5) Harmonized standards: **EN 13813:2002**

Notified bodies: **CSI SPA, N. 0497**

- 6) Performances declared:

Essential characteristics	Performances
Reaction to fire:	Class B_{FL}-s1
Release of corrosive substances:	CT
Water permeability:	w < 0,1 kg/(m²·h^{0,5})
Water vapour permeability:	NPD
Compressive strength:	C50
Flexural strength:	F10
Wear resistance:	AR0,5
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	(Shore D reduction < 50%) CR9, CR10 (Class II, change of colour, clearer) CR11, CR12 (Class II)

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Lorenzo Martino – Corporate Quality Management**

Milan, 21/12/2022



REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) No 1907/2006 and following amendments are indicated in the Safety Data Sheet that MAPEI makes available on the website along with this current Declaration of Performance.

DoP in Pdf format are available in the Mapei website.

Revision 1 notes:	Reaction to fire updated
-------------------	--------------------------

MAPEFLOOR CPU+/RT
CE MARKING
Annex to DoP N. CPR-IT1/0897



 0497	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
21 CPR-IT1/0897 EN 13813 MAPEFLOOR CPU+/RT <i>Three-component cementitious screed material modified by polymer for internal use in floor construction</i>	
Reaction to fire: Release of corrosive substances: Water permeability: Water vapour permeability: Compressive strength: Flexural strength: Wear resistance: Sound insulation: Sound absorption: Thermal resistance: Chemical resistance:	Class B _{FL} -s1 CT $w < 0,1 \text{ kg}/(\text{m}^2 \cdot \text{h}^{0,5})$ NPD C50 F10 AR0,5 NPD NPD NPD (Shore D reduction < 50%) CR9, CR10 (Class II, change of colour, clearer) CR11, CR12 (Class II)

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- NPD (No Performance Determined) values can be omitted by the CE marking,
- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.