

EKSPLUATĀCIJAS ĪPAŠĪBU DEKLARĀCIJA No.
CPR-IT1/0491

- 1) Unikāls produkta tipa identifikācijas kods: **Mapefloor I 302 SL**
- 2) Paredzētais pielietojums: **Divkomponentu grīdu izveides sastāvs iekštelpu grīdām**
- 3) Ražotājs: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Sistēma AVCP: **Sistēma 4**
Sistēma 3, ugunsdrošības noteikšanai
- 5) Vienotais standarts: **EN 13813:2002**

Izpildinstitūcijas: **Pilnvarotā laboratorija CSI S.p.A., N. 0497, veikusi novērtējumu (ugunsdrošības noteikšana), pamatojoties uz testa paraugiem, ko iesniedzis ražotājs.**

- 6) Deklarētās veiktspējas īpašības:

Būtiskākie raksturlielumi	Ekspluatācijas īpašības
Ugunsdrošība: Kairinošu sastāvdaļu izdalīšanās: Ūdens caurlaidība: Berzes noturība: Adhēzija Trieciennoturība: Skaņas izolētspēja: Skaņas absorbētspēja: Termālā noturība: Ķīmiskā noturība:	Klase B_{FL}- s1 SR NPD AR0,5 B2,0 IR20 NPD NPD NPD NPD

Augstāk norādītā produkta veiktspēja atbilst deklarētajām īpašībām.

Šī ekspluatācijas īpašību deklarācija ir izsniegta saskaņā ar Regulu (ES) Nr 305/2011, ar pilnu iepriekš norādītā ražotāja atbildību

Parakstīts ražotāja vārdā: **Paolo Murelli – Korporatīvā Kvalitātes Vadība**

Milāna, 28/04/2015

.....

EĪD PDF formātā ir pieejamas Mapei mājas lapā

Pārskats 1	Pielāgošana jaunam EID izkārtojumam - produkts bez izmaiņām
-------------------	--

 0497	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
14 CPR-IT1/0491 EN 13813- 2:2002 Mapefloor I 302 SL <i>Two-component synthetic resin screed material for internal use in floor construction</i>	
Reaction to fire: Release of corrosive substances: Water permeability: Wear resistance: Bond strength Impact resistance: Sound insulation: Sound absorption: Thermal resistance: Chemical resistance:	Class BFL-s1 SR NPD AR0,5 B2,0 IR20 NPD NPD NPD NPD

Piezīme:

MAPEI nodrošina šo pielikumu kopā ar EĪD, lai atvieglotu CE marķējuma skaidrojumu starptautiskajiem klientiem. Pievienotais CE marķējums var būt nedaudz atšķirīgs, salīdzinot ar to, kas norādīts uz attiecīgā iepakojuma vai dokumentācijas, jo:

- Dēļ grafiskā pielāgojuma uz iepakojuma vai izmantotās drukāšanas metodes,
- Dēļ valodu atšķirības (viens iepakojums vairākām valstīm),
- produkts ir jau krājumā uz brīdi, kad tiek ieviests CE marķējuma atjauninājums,
- Drukas kļūdas dēļ.

DECLARATION OF PERFORMANCE N. CPR-IT1/0491

- 1) Unique identification code of the product-type: **MAPEFLOOR I 302 SL**
- 2) Intended uses: **Two-component synthetic resin screed material for internal use in floor construction**
- 3) Manufacturer: **MAPEI S.p.A. – Via Cafiero, 22 – 20158 Milan – Italy - www.mapei.it**
- 4) Systems of AVCP: **System 4**
System 3 (for reaction to fire)
- 5) Harmonized standards: **EN 13813:2002**

Notified bodies: **the notified laboratory CSI S.p.A., N. 0497, carried out the assessment of the performance (reaction to fire) on the basis of testing on samples taken by the manufacturer.**

- 6) Performances declared:


Essential characteristics	Performances
Reaction to fire:	Class B _{fl} -s1
Release of corrosive substances:	SR
Water permeability:	NPD
Wear resistance:	AR0,5
Bond strength	B2,0
Impact resistance:	IR20
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**

Milan, 28/04/2015



DoP in Pdf format are available in the Mapei website.

Revision 1 notes:	Adaptation to new DoP layout – no change in the product
-------------------	---

MAPEFLOOR I 302 SL
CE MARKING
Annex to DoP N. CPR-IT1/0491



 0497	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it
14 CPR-IT1/0491 EN 13813:2002 MAPEFLOOR I 302 SL <i>Two-component synthetic resin screed material for internal use in floor construction</i>	
Reaction to fire:	Class Bfl-s1
Release of corrosive substances:	SR
Water permeability:	NPD
Wear resistance:	AR0,5
Bond strength	B2,0
Impact resistance:	IR20
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.