

**EKSPLUATĀCIJAS ĪPAŠĪBU DEKLARĀCIJA No: CPR-NO1/0086**

- Unikāls izstrādājuma tipa identifikācijas numurs: **CONFIX FIN**
- Tipa, partijas vai sērijas numurs vai kāds cits būvizstrādājuma identifikācijas elements, kā noteikts 11. panta 4. punktā: **Hidrauliska java (R3-CC)**
- Būvizstrādājuma paredzētais izmantojums vai izmantojumi saskaņā ar piemērojamo saskaņoto tehnisko specifikāciju, kā paredzējis ražotājs:  
**Produkts betona remontam, ēku strukturālajam remontam un civilās būvniecības darbiem**
- Ražotāja nosaukums, reģistrētais komercnosaukums vai reģistrētā preču zīme un kontaktadrese, kā noteikts 11. panta 5. punktā: **MAPEI AS – Vallsetvegen, 6 – 2120 Sagstua (Norway) [www.mapei.no](http://www.mapei.no)**
- Vajadzības gadījumā tā pilnvarotā pārstāvja vārds un kontaktadrese, kura pilnvaras attiecas uz 12. panta 2. punktā nosauktajiem uzdevumiem: **Nav piemērojams**
- Ekspluatācijas īpašību noturības novērtējuma un pārbaudes sistēma vai sistēmas, kā noteikts V pielikumā:  
**Sistēma 2+**  
**Sistēma 4, uguns noturības noteikšanai**
- Gadījumā, ja ekspluatācijas īpašību deklarācija attiecas uz būvizstrādājumu, kuram ir saskaņotais standarts: **Izpildinstitūcija nr. 1071 Sintef Building and Infrastructure veikusi sākotnējo ražotnes un ražošanas kvalitātes kontroles un uzraudzības pārbaudi, novērošanu un novērtēšanu, saskaņā ar sistēmu 2+ un ir izsniegusi rūpnīcas ražošanas kontroles atbilstības sertifikātu No. 1071– CPD – 1681.**
- Gadījumā, ja ekspluatācijas īpašību deklarācija attiecas uz būvizstrādājumu, kuram ir izdots Eiropas tehniskais novērtējums: **Nav piemērojams**
- Deklarētās ekspluatācijas īpašības

| Būtiskie raksturlielumi                                                                                                                                                                                                                                        | Ekspluatācijas īpašības                                                                                                                                                                                             | Saskaņota tehniskā specifikācija |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| <b>Spiedes noturība</b><br><b>Hlorīdu jonu saturs</b><br><b>Adhēzija</b><br><b>Noturība pret karbonizāciju</b><br><b>Elastības modulis</b><br><b>Termālā savienojamība</b><br><b>Kapilārā absorbētspēja</b><br><b>Bīstamas vielas</b><br><b>Uguns noturība</b> | <b>Klase R3</b><br><b>≤ 0,05%</b><br><b>≥ 1,5 MPa</b><br><b>Tests izturēts</b><br><b>≥ 15 GPa</b><br><b>≥ 1,5 MPa</b><br><b>≤ 0,5 kg*m<sup>-2</sup>*h<sup>-0,5</sup></b><br><b>Skat. DDL</b><br><b>Eiroklase A1</b> | <b>EN 1504-3:2005</b>            |

- Pielikuma 1. un 2. punktā norādītā izstrādājuma ekspluatācijas īpašības atbilst 9. punktā norādītajām deklarētajām ekspluatācijas īpašībām.

Par šo izdoto ekspluatācijas īpašību deklarāciju ir atbildīgs vienīgi 4. punktā norādītais ražotājs.

Parakstīts ražotāja vārdā:

**Trond Hagerud – Managing director**

(vārds, uzvārds, amats)

**Sagstua, 14/10/2019**

(izdošanas vieta un datums)

(paraksts)

## **CE MARKING according to CPR 305/2011 and EN 1504-3:2005**

|                                                                                                  |                                                                                                                                                           |
|--------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br><b>1071</b> | <br><b>Vallsetvegen 6, 2120 Sagstua (Norway)</b><br><b>www.mapei.no</b> |
| <b>13</b><br><b>CPR-NO1/0086</b><br><b>EN 1504-3:2005</b><br><b>CONFIX FIN</b>                   |                                                                                                                                                           |
| <i>Produkts betona remontam, ēku strukturālais remonts un civilās būvniecības darbi</i>          |                                                                                                                                                           |
| Spiedes noturība                                                                                 | Klase R3                                                                                                                                                  |
| Hlorīdu jonu saturs                                                                              | ≤ 0,05%                                                                                                                                                   |
| Adhēzija                                                                                         | ≥ 1,5 MPa                                                                                                                                                 |
| Noturība pret karbonizāciju                                                                      | Tests izturēts                                                                                                                                            |
| Elastības modulis                                                                                | ≥ 15 GPa                                                                                                                                                  |
| Termālā savienojamība                                                                            | ≥ 1,5 MPa                                                                                                                                                 |
| Kapilārā absorbētspēja                                                                           | ≤ 0,5 kg*m-2*h-0,5                                                                                                                                        |
| Bīstamas vielas                                                                                  | Skat. DDL                                                                                                                                                 |
| Uguns noturība                                                                                   | Eiroklase A1                                                                                                                                              |

## Declaration of performance: No. CPR-NO1/0086

1. Unique identification code of the product-type: **CONFIX Fin**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

**Hydraulic mortar based on hydraulic cement - (R3-CC)**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**For structural and non-structural repair in buildings and civil engineering works,**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI AS. – Vallsetvegen 5 – N-2120 Sagstua, Norway** **www.mapei.no**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 2+**  
**System 4 for reaction to fire**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**The Notified Body Sintef Building and Infrastructure No. 1071 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, under system 2+, and issued the certificates of conformity of the factory production control No. 1071-CPR-1681.**

8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**

9. Declared performance

| Essential characteristics            | Performance                                     | Harmonised technical specification |
|--------------------------------------|-------------------------------------------------|------------------------------------|
| <b>Compressive strength:</b>         | <b>Class R3</b>                                 | <b>EN 1504-3:2005</b>              |
| <b>Chloride ion content:</b>         | <b>≤ 0,05%</b>                                  |                                    |
| <b>Adhesive Bond:</b>                | <b>≥ 1,5 MPa</b>                                |                                    |
| <b>Carbonation resistance</b>        | <b>Pass</b>                                     |                                    |
| <b>Elastic modulus:</b>              | <b>≥ 15 GPa</b>                                 |                                    |
| <b>Thermal compatibility part 1:</b> | <b>≥ 1,5 MPa</b>                                |                                    |
| <b>Capillary absorption:</b>         | <b>≤ 0,5 kg*m<sup>-2</sup>*h<sup>-0,5</sup></b> |                                    |
| <b>Dangerous substances:</b>         | <b>see SDS</b>                                  |                                    |
| <b>Reaction to fire:</b>             | <b>Euroclass A1</b>                             |                                    |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.


This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: **Trond Hagerud – Managing Director**

(name and function)

**Sagstua, 14/10/2019**

(place and date of issue)

  
(signature)

## CE MARKING according to CPR 305/2011 and EN 1504-3:2005

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                               |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br>1071                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | <br>Vallsetvegen 6, 2120 Sagstua (Norway)<br><a href="http://www.mapei.no">www.mapei.no</a> |
| <p>12<br/>CPR-NO1/0086<br/>EN 1504-3:2005<br/>Confix Fin</p> <p>Concrete repair product for structural and non-structural repair, CC</p> <p>Compressive strength: Class R3 (<math>\geq 25,0</math> MPa)<br/>Chloride ion content: <math>\leq 0,05</math> %<br/>Adhesive bond: <math>\geq 1,5</math> MPa<br/>Carbonation resistance: passes<br/>Elastic modulus: <math>\geq 15</math> GPa<br/>Thermal compatibility part 1: <math>\geq 1,5</math> MPa<br/>Capillary absorption: <math>\leq 0,5 \text{ kg} \cdot \text{m}^{-2} \cdot \text{h}^{-0,5}</math><br/>Dangerous substances: See SDS<br/>Reaction to fire: Euroclass A1</p> |                                                                                                                                                                               |