

EKSPLUATĀCIJAS ĪPAŠĪBU DEKLARĀCIJA No: CPR-NO1/0064

- Unikāls izstrādājuma tipa identifikācijas numurs: **MAPEPOXY BI-IMP**
- Tipa, partijas vai sērijas numurs vai kāds cits būvizstrādājuma identifikācijas elements, kā noteikts 11. panta 4. punktā: **DIVKOMPONENTU BETONA INJEKCIJAS PRODUKTS, KAS TIEK RAŽOTS IZMANTOJOT REAKTĪVU POLIMĒRU SAISTVIELU - U(F1)W(1)(1/2/3/4)(5/30) (0)**
- Būvizstrādājuma paredzētais izmantojums vai izmantojumi saskaņā ar piemērojamo saskaņoto tehnisko specifikāciju, kā paredzējis ražotājs:
Produkts betona remontam un betona konstrukcijas aizsardzībai, noslēdzot plaisas un pārnesot spriedzi
- Ražotāja nosaukums, reģistrētais komercnosaukums vai reģistrētā preču zīme un kontaktadrese, kā noteikts 11. panta 5. punktā: **MAPEI AS – Vallsetvegen, 6 – 2120 Sagstua (Norway) www.mapei.no**
- Vajadzības gadījumā tā pilnvarotā pārstāvja vārds un kontaktadrese, kura pilnvaras attiecas uz 12. panta 2. punktā nosauktajiem uzdevumiem: **Nav piemērojams**
- Ekspluatācijas īpašību noturības novērtējuma un pārbaudes sistēma vai sistēmas, kā noteikts V pielikumā: **Sistēma 2+**
- Gadījumā, ja ekspluatācijas īpašību deklarācija attiecas uz būvizstrādājumu, kuram ir saskaņotais standarts: **Izpildinstitūcija nr. 1071 Sintef Building and Infrastructure veikusi sākotnējo ražotnes un ražošanas kvalitātes kontroles un uzraudzības pārbaudi, novērošanu un novērtēšanu, saskaņā ar sistēmu 2+ un ir izsniegusi rūpnīcas ražošanas kontroles atbilstības sertifikātu No. 1071– CPD – 1683.**
- Gadījumā, ja ekspluatācijas īpašību deklarācija attiecas uz būvizstrādājumu, kuram ir izdots Eiropas tehniskais novērtējums: **Nav piemērojams**
- Deklarētās ekspluatācijas īpašības

Būtiskie raksturlielumi	Ekspluatācijas īpašības	Saskaņota tehniskā specifikācija
Adhēzijas stiprība pie stiepes: Adhēzijas stiprība pie bīdes: Negaistošās vielas: Pārstiklošanās temp.: Izstrādājamība: - Plaisas platums - Plaisas mitruma pakāpe Ilgmūžība: Korozivitāte: Bīstamas vielas	> 2.5 N/mm² (pamatnes kohēzijas zudums) NPD > 95 % NPD No 0,1 mm Sauss, mitrs, slapjš, piepildīts ar ūdeni Tests izturēts Nav novērota korozivitāte NPD	EN 1504-5:2004

- Pielikuma 1. un 2. punktā norādītā izstrādājuma ekspluatācijas īpašības atbilst 9. punktā norādītajām deklarētajām ekspluatācijas īpašībām.
Par šo izdoto ekspluatācijas īpašību deklarāciju ir atbildīgs vienīgi 4. punktā norādītais ražotājs.

Parakstīts ražotāja vārdā:

Trond Hagerud – Izpilddirektors

(vārds, uzvārds, amats)

Sagstua, 01/12/2013

(izdošanas vieta un datums)

(paraksts)

CE MARKING according to CPR 305/2011 and EN 1504-5:2013

 1071	 Vallsetvegen 6, 2120 Sagstua (Norway) www.mapei.no																				
13 CPR-NO1/0064 EN 1504-5:2004 NAPEPOXY BI-IMP <i>Betona injekciju produkts , kura sastāvā ir reaktīva polimēru saistviela, betona konstrukciju remontam un aizsardzībai: U(F1)W(1)(1/2/3/4)(5/30)(0)</i> <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Adhēzijas stiprība pie stiepes:</td><td style="width: 50%; text-align: right;">≥ 2.5 N/mm² (pamatnes kohēzijas zudums)</td></tr> <tr> <td>Adhēzijas stiprība pie bīdes:</td><td style="text-align: right;">NPD</td></tr> <tr> <td>Negaistošās vielas:</td><td style="text-align: right;">> 95 %</td></tr> <tr> <td>Pārstiklošanās temp.:</td><td style="text-align: right;">NPD</td></tr> <tr> <td>Izstrādājamība:</td><td></td></tr> <tr> <td style="padding-left: 20px;">- Plaisas platums</td><td style="text-align: right;">No 0,1 mm</td></tr> <tr> <td style="padding-left: 20px;">- Plaisas mitruma pakāpe</td><td style="text-align: right;">Sauss, mitrs, slapjš, papildīts ar ūdeni</td></tr> <tr> <td>Ilgmūžība:</td><td style="text-align: right;">Tests izturēts</td></tr> <tr> <td>Korozivitāte:</td><td style="text-align: right;">Nav novērota korozivitāte</td></tr> <tr> <td>Bīstamas vielas</td><td style="text-align: right;">NPD</td></tr> </table>		Adhēzijas stiprība pie stiepes:	≥ 2.5 N/mm ² (pamatnes kohēzijas zudums)	Adhēzijas stiprība pie bīdes:	NPD	Negaistošās vielas:	> 95 %	Pārstiklošanās temp.:	NPD	Izstrādājamība:		- Plaisas platums	No 0,1 mm	- Plaisas mitruma pakāpe	Sauss, mitrs, slapjš, papildīts ar ūdeni	Ilgmūžība:	Tests izturēts	Korozivitāte:	Nav novērota korozivitāte	Bīstamas vielas	NPD
Adhēzijas stiprība pie stiepes:	≥ 2.5 N/mm ² (pamatnes kohēzijas zudums)																				
Adhēzijas stiprība pie bīdes:	NPD																				
Negaistošās vielas:	> 95 %																				
Pārstiklošanās temp.:	NPD																				
Izstrādājamība:																					
- Plaisas platums	No 0,1 mm																				
- Plaisas mitruma pakāpe	Sauss, mitrs, slapjš, papildīts ar ūdeni																				
Ilgmūžība:	Tests izturēts																				
Korozivitāte:	Nav novērota korozivitāte																				
Bīstamas vielas	NPD																				

Declaration of performance: No. CPR-NO1/0064

1. Unique identification code of the product-type: **MAPEPOXY BI -IMP**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

TWO-COMPONENT CONCRETE INJECTION PRODUCT FORMULATED WITH REACTIVE POLYMER BINDER

U (F1) W(1)(1/2/3/4) (5/30) (0)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Product for the repair and protection of concrete structure by force transmitting filling of cracks


4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI AS – Vallsetvegen 6 – 2120 Sagstua (Norway) www.mapei.no**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 2+**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
The Notified Body Sintef Building and Infrastructure No. 1071, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, under system 2+, and issued the certificates of conformity of the factory production control No. 1071– CPD – 1683.
8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance

Jjf

Essential characteristics	Performance	Harmonised technical specification
Adhesion by tensile bond strength: Adhesion by slant shear strength: Non volatile matter: Glass transition temperature: Workability: - crack width: - moisture state of the crack: Durability: Corrosion behaviour: Dangerous substances:	≥ 2,5 N/mm2 (cohesive failure in the substrate) NPD > 95 % NPD from 0,1 mm dry, damp, wet, waterfilled Pass deemed to have no corrosive effect NPD	EN 1504-5:2004

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of the manufacturer by: **Trond Hagerud – Managing Director**

Sagstua, 1/12/2013
(place and date of issue)


.....
(signature)

CE MARKING according to CPR 305/2011 and EN 1504-5:2013

 1071	 MAPEI Vallsetvegen 6, 2120 Sagstua (Norway) www.mapei.no																				
13 CPR-NO1/0064 EN 1504-5:2004 MAPEPOXY BI-IMP <i>Concrete injection product formulated with reactive polymer binder for the repair and protection of concrete structure:</i> <i>U(F1)W(1)(1/2/3/4)(5/30)(0)</i> <table><tr><td>Adhesion by tensile bond strength:</td><td>> 2.5 N/mm² (cohesive failure in the substrate)</td></tr><tr><td>Adhesion by slant shear strength:</td><td>NPD</td></tr><tr><td>Non volatile matter:</td><td>> 95 %</td></tr><tr><td>Glass transition temperature:</td><td>NPD</td></tr><tr><td>Workability:</td><td></td></tr><tr><td>- crack width:</td><td>from 0.1 mm</td></tr><tr><td>- moisture state of the crack</td><td>Dry, damp, wet, waterfilled</td></tr><tr><td>Durability:</td><td>Pass</td></tr><tr><td>Corrosion behaviour:</td><td>deemed to have no corrosive effect</td></tr><tr><td>Dangerous substances</td><td>NPD</td></tr></table>		Adhesion by tensile bond strength:	> 2.5 N/mm ² (cohesive failure in the substrate)	Adhesion by slant shear strength:	NPD	Non volatile matter:	> 95 %	Glass transition temperature:	NPD	Workability:		- crack width:	from 0.1 mm	- moisture state of the crack	Dry, damp, wet, waterfilled	Durability:	Pass	Corrosion behaviour:	deemed to have no corrosive effect	Dangerous substances	NPD
Adhesion by tensile bond strength:	> 2.5 N/mm ² (cohesive failure in the substrate)																				
Adhesion by slant shear strength:	NPD																				
Non volatile matter:	> 95 %																				
Glass transition temperature:	NPD																				
Workability:																					
- crack width:	from 0.1 mm																				
- moisture state of the crack	Dry, damp, wet, waterfilled																				
Durability:	Pass																				
Corrosion behaviour:	deemed to have no corrosive effect																				
Dangerous substances	NPD																				